
jlm Documentation

Release 0.1.1

Takafumi Arakaki

Apr 06, 2019

CONTENTS

1	Installation	1
2	Examples	3
2.1	Standard usage	3
2.2	Using MKL.jl-patched Julia and standard Julia side-by-side	3
3	Manual	5
3.1	Named Arguments	5
3.2	Sub-commands:	5

INSTALLATION

```
(v1.1) pkg> add JuliaManager
...
julia> using JuliaManager
julia> JuliaManager.install_cli()
...
```

You need to add `~/.julia/bin` to `$PATH` as would be messaged if it not.

EXAMPLES

2.1 Standard usage

```
$ cd PATH/TO/YOUR/PROJECT

$ jlm init
...

$ jlm run

      _ _ _ _ _      | Documentation: https://docs.julialang.org
    (_ )   | (_ ) (_ ) |
      _ _ _ _ _      | Type "?" for help, "]?" for Pkg help.
    | | | | | | | / _ ` | |
    | | | | | | | (_ | | | |
  _/ | \ _ ' _ | | | \ _ ' _ | | Official https://julialang.org/ release
 |__/_/              |

julia>
```

2.2 Using MKL.jl-patched Julia and standard Julia side-by-side

MKL.jl is a convenient way of using Intel's Math Kernel Library (MKL) with Julia. However, it still has some caveats and difficult to use standard Julia installation since precompilation cache are shared. This problem can be avoided by using **jlm** to separate compilation cache paths for MKL.jl and non-MKL.jl Julia. This way, both Julia installations can be used simultaneously without invoking repeated precompilation.

As **MKL.jl** overwrites its Julia installation, you need to create a dedicated Julia installation. Suppose it's done by

```
$ mkdir -p ~/opt/julia-mkl
$ cd ~/opt/julia-mkl
$ cd tar xf ~/Downloads/julia-1.1.0-linux-x86_64.tar.gz
```

Then create a project and install MKL.jl in it. Note that it is better be done in a separate project to avoid installing MKL.jl where standard (non-MKL.jl) Julia may accidentally instantiate and build it. This isolation is done by `--project=.`:

```
$ cd PATH/TO/PROJECT
$ ~/opt/julia-mkl/julia-1.1.0/bin/julia \
  --startup-file=no --compiled-modules=no --project=.
...
```

(continues on next page)

(continued from previous page)

```
(PROJECT) pkg> add https://github.com/JuliaComputing/MKL.jl
```

You may also need to run `pkg> build MKL`.

Finally, use *jlm* to isolate precompilation cache:

```
$ jlm init ~/opt/julia-mkl/julia-1.1.0/bin/julia
...
$ jlm run --project=.
      _ _(_)_ | Documentation: https://docs.julialang.org
  (_ ) | (_ ) |
    _ _ _ | | _ _ _ | Type "?" for help, "]?" for Pkg help.
  | | | | | | / _ ` | |
  | | | _ | | | ( _ | | Version 1.1.0 (2019-01-21)
 _/ | \_ ' _| _| \_ ' _| Official https://julialang.org/ release
|__/_/ |
```

(This may cause (re)compilation of cache files if you import some packages in `~/.julia/config/startup.jl`.)

In Julia REPL, you can check if *jlm* is using the correct version of Julia by

```
julia> Base.julia_cmd().exec[1]
"/home/USER/opt/julia-mkl/julia-1.1.0/bin/julia"

julia> using LinearAlgebra

julia> BLAS.vendor()
:mkl
```


Command line interface to manage Julia's system images.

```
usage: jlm [-h] [--version] [--dry-run] [--verbose] [--pdb] [--jlm-dir PATH]
          {run,init,set-default,set-sysimage,unset-sysimage,create-default-sysimage,
  ↪ install-backend,update-backend,info,locate}
  ...
```

3.1 Named Arguments

--version	show program's version number and exit
--dry-run	Default: False
--verbose, -v	Default: False
--pdb	Default: False
--jlm-dir	Specify the <code>.jlm</code> directory which is created by <code>jlm init</code> and stores information for <code>jlm</code> . By default, <code>.jlm</code> directory found in the nearest “ancestor” directory is used. Run <code>jlm locate dir</code> to locate the actual directory that would be used.

3.2 Sub-commands:

3.2.1 run

Run `julia` executable with appropriate system image.

```
jlm run [-h] [julia] [arguments [arguments ...]]
```

Positional Arguments

julia	The name of Julia executable on <code>\$PATH</code> or a path to the Julia executable.
arguments	Arguments and options passed to <code>julia</code> . Non-option like argument (i.e., the ones <i>not</i> starting with <code>-</code>) following <code>run</code> is always interpreted as a Julia executable. To pass a file path to Julia, use <code>--</code> as the first argument to <code>run</code> ; i.e. <code>jlm ... run -- PATH/TO/FILE.jl</code> If you pass <code>julia</code> to <code>run</code> , there

is no need to pass `--` since the argument parsing for `jlm` automatically ends at this point.

If argument `julia` is not given, the default executable configured by `jlm init` is used.

3.2.2 init

Initialize `jlm`.

```
jlm init [-h] [--sysimage SYSIMAGE] [julia]
```

Positional Arguments

julia The name of Julia executable on `$PATH` or a path to the Julia executable.

Named Arguments

--sysimage, -J The path to system image.

`jlm init` does:

- Create a data store (`.jlm` directory).
- Install `JuliaManager.jl` if it is not installed for `<julia>`.
- Compile the “patched” default system image (see note below) for `<julia>` if not already found and `--sysimage|-J` is not given. This can be done separately by `jlm compile-default-sysimage`.
- Set the system image to be used for `<julia>`. This can be re-done later by `set-sysimage`.

Note: `jlm` compiles the system image with a patch that does [Suggestion: Use different precompilation cache path for different system image by tkf · Pull Request #29914 · JuliaLang/julia](#)

3.2.3 set-default

Set default Julia executable to be used.

```
jlm set-default [-h] julia
```

Positional Arguments

julia The name of Julia executable on `$PATH` or a path to the Julia executable.

3.2.4 set-sysimage

Set system image for `julia`.

```
jlm set-sysimage [-h] [julia] sysimage
```

Positional Arguments

julia	The name of Julia executable on <code>\$PATH</code> or a path to the Julia executable.
sysimage	The path to system image.

3.2.5 unset-sysimage

Unset system image for `julia`.

```
jlm unset-sysimage [-h] [julia]
```

Positional Arguments

julia	The name of Julia executable on <code>\$PATH</code> or a path to the Julia executable.
--------------	--

3.2.6 create-default-sysimage

Compile default system image for `julia`.

```
jlm create-default-sysimage [-h] [--force] [julia]
```

Positional Arguments

julia	The name of Julia executable on <code>\$PATH</code> or a path to the Julia executable.
--------------	--

Named Arguments

--force, -f	Re-compile default system image for <code>julia</code> even if it already exists. Default: False
--------------------	---

3.2.7 install-backend

Install `JuliaManager.jl` for this `julia`.

```
jlm install-backend [-h] [julia]
```

Positional Arguments

julia	The name of Julia executable on <code>\$PATH</code> or a path to the Julia executable.
--------------	--

3.2.8 update-backend

Update `JuliaManager.jl` for this `julia`.

```
jlm update-backend [-h] [julia]
```

Positional Arguments

julia The name of Julia executable on `$PATH` or a path to the Julia executable.

3.2.9 info

Print information about jlm setup.

```
jlm info [-h]
```

3.2.10 locate

Show paths to related files and directories

```
jlm locate [-h] {sysimage,base,dir,home-dir} ...
```

Sub-commands:

sysimage

Print system image that would be used for julia.

```
jlm locate sysimage [-h] [julia]
```

Positional Arguments

julia The name of Julia executable on `$PATH` or a path to the Julia executable.

base

Print directory for which `jlm init` was executed.

```
jlm locate base [-h]
```

dir

Print directory in which jlm information is stored.

```
jlm locate dir [-h]
```

home-dir

Print directory in which jlm global information is stored.

```
jlm locate home-dir [-h]
```